

**1. COMPANY AND PRODUCT IDENTIFICATION**

**Product Name** : DISOL 65  
**Application Uses** : Industrial Solvent containing heavy aromatics for Asphalt Industries  
**Company Name** : Verasuwan Company Limited  
**Company Address** : 53/2, 53/8 Moo 5, Setthakij 1 Road, Nadee, Muang Samutsakorn 74000, Thailand  
**E-mail** : verasuwan@gmail.com  
**Emergency Telephone** : (+66)-34-468-801

**2. HAZARDS IDENTIFICATION**

**GHS classification** : Flammable Liquids, Category 4  
 Specific target organ systemic toxicity (Single Exposure), Category 3  
 Narcotic effects.  
 ASPIRATION Hazard, Category 1  
 CARCINOGENICITY, Category 2  
 AQUATIC TOXICITY (ACUTE). Category 2  
 AQUATIC TOXICITY (CHRONIC), Category 2

**GHS label elements Symbols**


**Signal words** : **Danger**

**GHS Hazard statements**

**Physical hazards** : H227 Combustible Liquid  
**Health hazards** : H304 May be fatal if swallowed and enters airways  
 H316 Causes mild skin irritation  
 H336 May cause drowsiness or dizziness  
 H351 Suspected of causing cancer.  
**Environmental hazards** : H401 Toxic to aquatic life  
 H411 Toxic to aquatic life with long lasting effects.

**GHS Precautionary statements**

**Prevention** : P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P241 Use explosion-proof electrical/ventilating/lighting equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge  
 P261 Avoid breathing dust/fume/vapors/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.



|          |  |
|----------|--|
|          | P280 Wear protective gloves/protective clothing/eye protection/face protection.  |
|          | P281 Use personal protective equipment as required.  |
|          | P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  |
| Response | : P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.<br>P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.<br>P332+P313 If skin irritation occurs, get medical advice/attention.<br>P308+P313 If exposed or concerned, get medical advice/attention.<br>P304+P340 IF INHALED remove to fresh air and keep at rest in a position comfortable for breathing.<br>P312 Call a POISON CENTRE or doctor/physician if you fell unwell.<br>P370+P378 In case of fire: Use appropriate media for extinction.<br>P331: Do NOT induce vomiting<br>P391 Collect spillage. |
| Storage  | : P403+P235 Store in a well-ventilated place. Keep cool.<br>P233 Keep container tightly closed.<br>P405 Store locked up.   |
| Disposal | : P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.   |

### 3. COMPOSITION AND INFORMATION ON INGREDIENTS

**Chemical Identity** : Solvent Naphtha (Petroleum) with heavy aromatics  
**CAS No.** : 64742-95-6

Compositions:

| <b>Name</b>          | <b>CAS No.</b> | <b>by Weight</b> |
|----------------------|----------------|------------------|
| Benzene              | 200-753-7      | < 0.5            |
| Petroleum Distillate | 265-185-4      | 50-60            |
| Heavy Aromatics      | 64742-94-5     | 40-50            |

### 4. FIRST AID MEASURES

**General Information** : Not expected to be health hazard when used under normal conditions. Keep victim calm. Obtain medical treatment immediately

**Inhalation** : Remove to fresh air. If rapid recovery does not occur, transport to the nearest medical facility for additional treatment

**Eye Contact** : Flush eyes with water while holding eyelids open. Rest eyes for 30 minutes. If redness, burning, blurred vision, or swelling persist, transport to the nearest medical facility for additional treatment.



- Ingestion** : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3° C), shortness of breath, chest congestion or continued coughing or wheezing.
- Note to physicians** : Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing. Breathing of high vapor concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.
- Immediate medical attention and special treatment** : Causes central nervous system depression. Dermatitis may result from prolonged or repeated exposure. Potential for chemical pneumonitis. Call a doctor or poison control center for guidance.

## 5. FIRE FIGHTING MEASURES

**Clear fire area of all non-emergency personnel.**

**Extinguish media** : Foam, water sprat or fog. Dry chemical powder, carbon dioxide, sand Or earth may be used for small fires only. Do not discharge extinguishing water into the aquatic environment.

**Unsuitable Extinguishing** : Do not use water in a jet

**Media**

**Specific Hazards** : Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. The vapor is heavier than air, spreads along the ground and distant ignition is possible.

**Protective Equipment** : Wear full protective clothing and self-contained breathing apparatus.

**Additional information** : Keep adjacent containers cool by spraying with water.

## 6. ACCIDENTAL RELEASE MEASURES

Observe all relevant local and international regulations.

- Personal precautions, protective equipment and emergency procedures** : Avoid contact with spilled or released material. Immediately remove all contaminated clothing. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Material Safety Data Sheet.
- Environmental precautions** : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment (of product and fire fighting water) to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapor or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas indicator.
- Methods and material for containment and clean Up** : For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
- Additional advice** : See Chapter 13 for information on disposal. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

## 7. HANDLING AND STORAGE

- General Precautions** : Avoid breathing vapors or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. On guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Precautions for Safe Handling** : Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Avoid contact with skin, eyes, and



- clothing. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/sec until fill pipe submerged to twice its diameter, then  $\leq 7$  m/sec). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.
- Conditions for safe storage** : Must be stored in a diked (bunded) area. Bulk storage tanks should be diked (bunded). Keep away from flammables, oxidizing agents, and corrosives.  
Storage Temperature: Ambient.
- Product transfer** : Keep containers closed when not in use. Do not use compressed air for filling, discharging or handling.
- Recommended materials** : For containers, or container linings use mild steel, stainless steel. For container paints, use epoxy paint, zinc silicate paint.
- Unsuitable materials** : Avoid prolonged contact with natural, butyl or nitrile rubbers.
- Container advice** : Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.
- Other advice** : Ensure that all local regulations regarding handling and storage facilities are followed.

## 8. EXPOSURE CONTROL / PERSONAL PROTECTION

- Appropriate Engineering Controls** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Use sealed systems as far as possible. Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines /limits. Local exhaust ventilation is recommended. Firewater monitors and deluge systems are recommended. Eye washes and showers for emergency use.
- Individual protection Measures** : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
- Respiratory Protection** : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for organic gases and vapors [boiling point  $>65$  °C (149 °F)] meeting EN14387. Where

|                           |  |
|---------------------------|--|
|                           | air-filtering respirators are unsuitable (e.g., airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus.  |
| <b>Hand protection</b>    | : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739, AS/NZS:2161) made from the following materials may provide suitable chemical protection: Longer term protection: Nitrile rubber gloves<br>Incidental contact/Splash protection: PVC or neoprene rubber gloves<br>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. |
| <b>Body protection</b>    | : Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.  |
| <b>Monitoring Methods</b> | Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.   |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |  |
|---|--|
| Physical state and appearance                                   | : Pale yellow liquid   |
| Odor  | : Aromatic   |
| Odor threshold  | : Data not available   |
| pH  | : Not applicable   |
| Boiling Range   | : Typical 170 – 310 °C   |
| Pour point  | : Typical -20 °C   |
| Flash point   | : Typical 45 °C (ASTM D-93, PMCC)                              |
| Explosion / Flammability  | : 0.6 – 7.0 %Vol   |
| Limits in air   |  |
| Auto-ignition temperature                                       | : 300 °C / 572 °F (ASTM E-659)                                 |
| Vapor pressure  | : < 1.5 kPa at 20 °C / 68 °F                                   |
| Specific gravity  | : 0.810 – 0.850 at 15 °C / 60 °F                               |
| Density   | : Typical 835 kg/m <sup>3</sup> at 15 °C / 60 °F (ASTM D-1298) |
| Water Solubility  | : Insoluble  |
| n-octanol/water as partition coefficient (log P <sub>ow</sub> ) | : 2.6 – 5.3  |
| Decomposition Temperature                                       | : Stable under normal conditions of use                        |
| Kinematic viscosity   | : 1.68 – 1.75 mm <sup>2</sup> /s at 25 °C / 77 °F              |
| Vapor density (air=1)   | : 3.80   |
| Evaporation rate (nBuAc=1)                                      | : < 0.5 (ASTM D 3539)  |
| Volatile organic carbon   | : 65% (EC/1999/13)   |

## 10. STABILITY AND REACTIVITY

|                                    |   |   |
|------------------------------------|---|---|
| Reactivity                         | : | Data not available  |
| Stability                          | : | Stable under normal conditions of use.  |
| Possibility of hazardous reactions | : | Data not available  |
| Conditions to avoid                | : | Avoid heat, sparks, open flames and other ignition sources.<br>Prevent vapor accumulation.  |
| Material to avoid hazardous        | : | Strong oxidizing agents   |
| Decomposition products             | : | Thermal decomposition is highly dependent on conditions.<br>A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation. |
| Sensitivity to static discharge    | : | Yes, in certain circumstances product can ignite due to static electricity.   |

## 11. TOXICOLOGICAL INFORMATION

|   |   |  |
|---|---|--|
| Basis for Assessment                              | : | Information given is based on product testing, and/or similar products, and/or components.   |
| Routes of exposure                                | : | Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.  |
| Acute Toxicity                                    | : | Low toxicity: LD50 > 5000 mg/kg , Rat  |
| Acute Dermal Toxicity                             | : | Low toxicity   |
| Acute Inhalation Toxicity                         | : | Expected to be low toxicity if inhaled.<br>High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. |
| Skin corrosion/irritation                         | : | Not irritating to skin.<br>Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.                                      |
| Serious eye damage/irritation                     | : | Not irritating to eye.   |
| Respiratory Irritation                            | : | Inhalation of vapors or mists may cause irritation to the respiratory system.  |
| Skin or respiratory Sensitization                 | : | Not a skin sensitizer.<br>Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.                         |
| Germ cell mutagenicity                            | : | Not mutagenic.   |
| Carcinogenicity                                   | : | Limited evidence of carcinogenic effect. (Naphthalene)   |
| Reproductive and Developmental toxicity           | : | Not expected to impair fertility<br>Causes foetotoxicity in animals at doses, maternally toxic.<br>May cause drowsiness or dizziness                     |
| Specific target organ toxicity- single exposure   | : | Kidney – caused kidney effects in male rats which are not  |
| Specific target organ toxicity- repeated exposure | : | considered relevant to humans.   |

**12. ECOLOGICAL INFORMATION**

|                               |   |  |
|-------------------------------|---|--|
| Basis for assessment          | : | Incomplete ecotoxicological data are available for this product. The information given below is based partly on a knowledge of the components and the ecotoxicology of similar products. |
| Acute Toxicity                |   |  |
| Fish                          | : | Toxic: 1 < LC/EC/IC50 <= 10 mg/l   |
| Aquatic Invertebrates         | : | Toxic: 1 < LC/EC/IC50 <= 10 mg/l   |
| Algae                         | : | Toxic: 1 < LC/EC/IC50 <= 10 mg/l   |
| Microorganisms                | : | Expected to be toxic: 1 < LC/EC/IC50 <= 10 mg/l  |
| Chronics Toxicity             |   |  |
| Fish                          | : | NOEC/NOEL expected to be >0.1 - <=1.0 mg/l (based on modeled data)   |
| Aquatic invertebrates         | : | NOEC/NOEL expected to be >0.1 - <=1.0 mg/l (based on modeled data)   |
| Persistence and degradability | : | Biodegradable.<br>Oxidizes rapidly by photo-chemical reactions in air.   |
| Bioaccumulative potential     | : | Has potential to bioaccumulate.  |
| Mobility                      | : | Adsorbs to soil and has low mobility. Floats on water.   |

**13. DISPOSAL CONSIDERATIONS**

|                    |   |   |
|--------------------|---|---|
| Material Disposal  | : | Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.<br>Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water. |
| Container Disposal | : | Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not, puncture, cut, or weld uncleaned drums. Send to drum recoverer or metal reclaimer.  |
| Local Legislation  | : | Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.  |

**14. TRANSPORT INFORMATION**

|                                  |   |           |
|----------------------------------|---|-----------|
| Land (as per ADR classification) | : | Regulated |
| Class                            | : | 3         |
| Packing group                    | : | III       |
| Hazard Identification no.        | : | 30        |
| UN no.                           | : | 1300      |



Danger label (primary risk) : 3  
 Proper shipping name : Mineral Turpentine, Turpentine substitute  
 Environmentally Hazardous : Yes

**UMDG**

Identification number : UN 1300  
 Proper shipping name : Turpentine substitute  
 Class / Division : 3  
 Packing group : III  
 Marine pollutant : Yes

**IATA**

(Country variation may apply)

UN no. : 1300  
 Proper shipping name : Turpentine substitute  
 Class / Division : 3  
 Packing group : III

**Sea (Annex II of MARPOL 73/78 and the IBC code)**

Pollution Category : Annex I  
 Ship Type : 2  
 Product name : White Spirit, high aromatics, Aromatic naphtha (having less than 10 % benzene)  
 Special Precaution : Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

**15. Regulatory Information**

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

**Chemical Inventory Status**

DSL : Listed  
 INV : Listed  
 TSCA : Listed  
 EINECS : Listed 265-198-5  
 KECI (KR) : Listed KE-31656  
 PICCS (PH) : Listed

## 16. Other Information

National Fire Protection Association (USA) :



### GHS Hazard Statements

|      |   |  |
|------|---|--|
| H225 | : | Highly Flammable liquid and vapor.   |
| H226 | : | Flammable liquid and vapor.  |
| H302 | : | Harmful if swallowed.  |
| H304 | : | May be fatal if swallowed and enters airways.  |
| H315 | : | Causes skin irritation.  |
| H319 | : | Causes serious eye irritation.   |
| H332 | : | Harmful if inhaled.  |
| H335 | : | May cause respiratory irritation.  |
| H340 | : | May cause genetic defects.   |
| H350 | : | May cause cancer (state route of exposure if it is conclusively proven that no routes of exposure cause hazard).             |
| H351 | : | Suspected of causing cancer. (state route of exposure if it is conclusively proven that no routes of exposure cause hazard). |
| H372 | : | Causes damage to organs through prolong or repeated exposure.  |
| H400 | : | Very toxic to aquatic life.  |
| H410 | : | Very toxic to aquatic life with long lasting effects.  |
| H411 | : | Toxic to aquatic life with long lasting effects.   |

**Disclaimer:** This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.